



MiniPro®

**Perfect for small lawns
and landscapes.**

- ▶ Revolutionary Patented Top Arc Set – Simplified arc set allows for wet or dry adjustment in seconds
- ▶ 1/2" Inlet – Replaces all standard mini rotors and pop-up sprays
- ▶ Adjustable to 360° – Full range of adjustment from 40° to 360°
- ▶ Patented Top Arc Set Degree Markings – Clearly indicates the current watering pattern and simplifies arc set adjustment
- ▶ Time Proven Patented Reversing Mechanism – Assures continuous reverse and return...over a 35 year history
- ▶ Rubber Cover – Seals out dirt and increases product durability
- ▶ Optional Check Valve – Prevents low head drainage



EASY ARC SETTING

Arc Selection
40° to 360°

Adjust From
Left Start

INLET SIZE
1/2"

RADIUS
18' – 33'

FLOW RATE
0.8 – 3.3 GPM

BEST IN THE INDUSTRY
WARRANTY
7 YEARS



MiniPro®

The name says it all: Pro performance and pro features on a smaller scale. That's why MiniPro® is the professional's choice for small lawn and landscape areas.

The MiniPro has an arc adjustment of 40° to 360°. Adjusting that pattern is easy because of the top arc set degree indications and the spray direction arrow located on the sprinkler head. Simply insert a flat blade screwdriver into the arc adjustment slot and adjust as desired. The sprinkler can be adjusted wet or dry -- before installation and after installation with the water on or off.

When considering the MiniPro gear-driven rotor for your next small lawn or landscape project, think water efficiency and flexibility. Available in 4", 6" and 12" heights, it is also available in a reclaimed water model (RCW) and comes with five (5) numerically coded interchangeable nozzles.



Performance Data – U.S.

NOZZLE	PRESSURE	RADIUS	FLOW	PRECIP in/hr	
	PSI	FEET	GPM	■	▲
#0.75	30	18	0.8	0.48	0.55
	40	19	0.8	0.43	0.49
	50	20	0.9	0.43	0.50
#1.0	30	26	0.9	0.26	0.30
	40	27	1.2	0.32	0.37
	50	27	1.3	0.34	0.40
#1.5 Pre-Installed	30	27	1.5	0.40	0.46
	40	27	1.8	0.48	0.55
	50	28	2.0	0.49	0.57
#2.0	30	29	2.0	0.46	0.53
	40	30	2.3	0.49	0.57
	50	31	2.7	0.54	0.62
#3.0	30	32	3.0	0.56	0.65
	40	33	3.4	0.60	0.69
	50	33	3.8	0.67	0.78

Performance Data – Metric

NOZZLE	PRESSURE	RADIUS	FLOW	PRECIP mm/hr	
	BAR	METERS	L/M	■	▲
#0.75	2,1	5,5	3,0	12	14
	2,8	5,8	3,0	11	13
	3,4	6,1	3,4	11	13
#1.0	2,1	7,9	3,4	7	8
	2,8	8,2	4,5	8	9
	3,4	8,2	4,9	9	10
#1.5 Pre-Installed	2,1	8,2	5,7	10	12
	2,8	8,2	6,8	12	14
	3,4	8,5	7,6	12	14
#2.0	2,1	8,8	7,6	12	13
	2,8	9,1	8,7	12	14
	3,4	9,4	10,2	14	16
#3.0	2,1	9,8	11,4	14	17
	2,8	10,1	12,9	15	18
	3,4	10,1	14,4	17	20

Specifications	
Radius	17' – 30' (5,2 – 9,2 m)
Flow Rate	0.8 – 3.3 GPM (3,0 – 12,5 LPM)
Pressure Range	20 – 70 PSI (1,4 – 4,8 bar)
Precipitation Rate	.26 – .60 in/hr (6,6 – 15,2 mm/hr)
Arc Setting Range	40° – 360°
Nozzle Trajectory	25°
Nozzles Included	5
4"	Retracted height: 6" (15,2 cm) Riser height: 4" (10,2 cm)
6"	Retracted height: 8 3/8" (21,3 cm) Riser height: 6" (15,2 cm)
12"	Retracted height: 15 1/4" (38,7 cm) Riser height: 12" (30,5 cm)
Inlet	1/2" (1,3 cm) Female Thread NPT
Warranty	7 years

Models

13003	MiniPro® – 4" (10,2 cm)
13006	MiniPro® – 6" (15,2 cm)
13012	MiniPro® – 12" (30,5 cm)

How to Specify

MODELS	OPTIONS
13003	-CV ▶ Check Valve
13006	-NN ▶ No Nozzle
13012	-RCW ▶ Reclaimed Water use

Examples: 13003-NN, 13006-RCW-CV



Sold with 5 interchangeable nozzles