PVC-U Adaptor fittings, metric - BSPP

PVC-U Raccordi di passaggio, metrico - BSPP

REDUCING BUSH
RIDUZIONE CORTA

Rev. Oct 2020



Code	d	Rp	L min	Z max	H	PN	Weight (g)
RGRRCG025B	25	1/2"	15	4	19	16	8
RGRRCG032C	32	3/4"	16,3	5,7	22	16	10
RGRRCG040D	40	1"	19,1	6,9	26	16	17
RGRRCG050E	50	1"1/4	21,4	9,6	31	16	30
RGRRCG063F	63	1"1/2	21,4	16,6	38	16	81
RGRRCG075G	75	2"	25,7	18,3	44	16	85
RGRRCG090H	90	2"1/2	30,2	20,8	51	16	165
RGRRCG110I	110	3"	33,3	27,7	61	16	238

Thread according to ISO 228-1 / *Filettatura secondo ISO 228-1*

NSF and WRAS certifications: only for valves with EPDM seals. Certifications and approvals are related to items declared on Official Listing or certificates. /
Certificazioni NSF e WRAS: valide solo per le valvole con guarnizioni EPDM. Le certificazioni si riferiscono ai prodotti dichiarati nelle Official Listing o sui certificati stessi.

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions given are nominal, while changes can be done on the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' on the revision date stated on the sheet. Updates will not be issued automatically. This information is not intended to have any legal effect, whether by way of advice, representation or warranty (express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication you must do so at your own risk. All rights reserved. Copyright in this publication belongs to Polypipe Italia and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person without prior consent. EFFAST is a registered trademark."

Polypipe Italia
Loc. Pianmercato 5C-5D-5H, 16044 Cicagna (GE), Italy
Tel: +39 0185 92399 E-mail: support@effast.com

www.effast.com